

MATERIAL SAFETY DATA SHEET

Date-Issued : 04/08/2004
MSDS Ref. No : 691A (63/37)
Date-Revised : 06/11/2010
Revision No : 3

Solder Paste Type 691A

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Solder Paste Type 691A
PRODUCT DESCRIPTION: No Clean Solder Paste

MANUFACTURER

Qualitek International, Inc.
 315 Fairbank St.
 Addison, IL 60101
Product Stewardship: (630) 628-8083

2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Content</u>	<u>CAS</u>	<u>EINECS</u>
Tin*	62.5 - 63.5	7440-31-5	231-141-8
Lead*	36.5 - 37.5	7439-92-1	231-100-4

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

EYES: Fumes from this and other soldering products may cause eye irritation.

SKIN: Fumes from this and other soldering products may cause skin irritation.

INGESTION: Ingestion of this or other soldering products may cause headache, nausea, and muscular pain.

INHALATION: Inhalation of the fumes from this or other soldering products may cause headache, nausea and muscular pain.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

SKIN: Discomfort or rash.

INHALATION: Irritation of the pulmonary system.

CHRONIC: Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain.

Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and damage to the mucous membranes.

CARCINOGENICITY: Not listed as a carcinogen by NTP, OSHA, or ACGIH. IARC classifies "lead and its compounds" as a Group 2B Carcinogen (possibly carcinogenic to humans).

MEDICAL CONDITIONS AGGRAVATED: Pre-existing conditions of the lungs, kidneys, nervous system and possibly reproductive systems; diseases of the blood forming organs

ROUTES OF ENTRY: Inhalation, ingestion, eye or skin contact.

4. FIRST AID MEASURES

EYES: MOLTEN PRODUCT: Cool burns with plenty of low-pressure water. Get immediate medical attention. **SOLID PRODUCT:** Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation develops.

SKIN: MOLTEN PRODUCT: Immediately cool skin burns with water and cold packs for at least 15 minutes. Do not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. **SOLID PRODUCT:** Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

INGESTION: If person is conscious, immediately give 2 glasses of water. Do not induce vomiting. Get immediate medical attention.

INHALATION: If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek medical attention.

COMMENTS: If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this MSDS to the physician/health care professional.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: > 98.3°C (209°F)

FLAMMABLE LIMITS: Not Established

AUTOIGNITION TEMPERATURE: > 227°C (440°F)

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, or alcohol-type foam.

EXPLOSION HAZARDS: Closed containers may explode when exposed to fire conditions.

FIRE FIGHTING EQUIPMENT: Self contained breathing apparatus with full face piece operated in positive pressure demand mode, appropriate turn-out gear and chemical resistant personal protective equipment is recommended.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Scoop up material and deposit in appropriate containers. Clean up residual spill area with isopropanol or detergent water.

RELEASE NOTES: Avoid repeated or prolonged breathing or skin contact. Wash hands immediately, and remove material from under the fingernails.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Do not store or use near sparks or open flames. Keep containers tightly closed and upright when not in use in order to prevent leakage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES:

OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200)

<u>Chemical Name</u>	<u>EXPOSURE LIMITS</u>						
	<u>OSHA PEL</u>		<u>ACGIH TLV</u>		<u>Supplier OEL</u>		
	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>	<u>ppm</u>	<u>mg/m³</u>	
Tin*	TWA	NL	2.00	NL ppm	2.00	NL ppm	NL
		ppm ^[1]	mg/m ³		mg/m ³		mg/m ³
	STEL	NL ppm	NL	NL ppm	NL	NL ppm	NL
			mg/m ³		mg/m ³		mg/m ³
Lead*	TWA	NL ppm	0.05	NL ppm	0.15	NL ppm	NL
			mg/m ³		mg/m ³		mg/m ³
	STEL	NL ppm	NL	NL ppm	NL	NL ppm	NL
			mg/m ³		mg/kg		mg/m ³

OSHA TABLE COMMENTS:

1. NL = Not Listed

ENGINEERING CONTROLS: General (mechanical) room ventilation is expected to be satisfactory where this product is stored and handled and in closed equipment. Special local ventilation is needed at points where vapors can be expected to escape into the workplace air.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Face shield, safety glasses with side shield or chemical splash goggles. When working with molten material, face shield is recommended.

SKIN: Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

RESPIRATORY: Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.

PROTECTIVE CLOTHING: Protective clothing and safety shoes as necessary to minimize contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

OTHER USE PRECAUTIONS: Eye wash station and quick drench safety shower in immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Mild.

APPEARANCE: Paste.

COLOR: Metallic gray.

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: 300°C (572°F)(vehicle)

MELTING POINT: (Please refer to Technical Bulletin for specific alloy data)

SOLUBILITY IN WATER: Partially Soluble

SPECIFIC GRAVITY: 3.5 to 5.5 (water=1)

10. STABILITY AND REACTIVITY

STABILITY: Stable under ordinary use and storage conditions.

POLYMERIZATION: Will not occur under normal use and storage conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: May emit toxic fumes of carbon monoxide and carbon dioxide.

INCOMPATIBLE MATERIALS: Strong acids and strong oxidizers should be avoided..

11. TOXICOLOGICAL INFORMATION

GENERAL COMMENTS: No toxicological information available at this time.

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: No information on ecological toxicity or biodegradability is available at this time.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated by DOT

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Chronic health hazard.

313 REPORTABLE INGREDIENTS: This product may contain one or more of the following: Lead CAS# 7439-92-1, Silver CAS# 7440-22-4, or Antimony CAS# 7440-36-0. Exact weight percentages can be determined from the product label.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

CALIFORNIA PROPOSITION 65: The following components are known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986.": Lead CAS# 7439-92-1

16. OTHER INFORMATION

APPROVED BY: P. Han **TITLE:** Technical Director

PREPARED BY: J. Saleda-Layton

INFORMATION CONTACT: (630) 628-8083

REVISION SUMMARY Revision #: 3 This MSDS replaces the January 29, 2010 MSDS. Any changes in information are as follows: In Section 1 Approved by Title MSDS Number Prepared By

HMIS RATING

HEALTH:		2
FLAMMABILITY:		1
PHYSICAL HAZARD:		0
PERSONAL PROTECTION:		B

MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Material Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Material Safety Data Sheets as a source of hazards information and response.